# Working Alone

#### Not Recommended, but Sometimes Necessary

Jeff Welton, CBRE

Regional Sales Manager, Eastern U.S.



### Overview

- More companies are having to do more with less
- Engineers are getting older
- Safety Implications
- Legal Implications
- Security issues
  - Personal
  - Site
  - IT



### **Graying Talent**

- What does it mean?
  - In the 10 year period between 2001 and 2011, the average age of broadcast engineers as a group rose by 4 years.
    - If this continues, very shortly, there will be a shortage of engineering personnel, as older engineers retire.
    - In addition, unless there is a significant upswing in mentoring, essential skills will be lost the ability to work on equipment with HV sections and tune in an AM array, to name two.



### Lower Budgets

 Fifty – or even 25 – years ago, manned transmitter sites were quite common and engineering staff tended to include both RF and audio engineers.



Photo of WCCO transmitter control point, © <u>www.oldradio.com</u> – originally taken by M. Durenberger





# More Reliable Equipment

- The advent of solid state electronics has permitted redundancy resulting in fewer off-air type situations.
- Modular construction permits repairs to be carried out while on air, during daytime hours.
- Lower operating voltages tend to make equipment safer to work on – in general.



# More IT, less RF

- More and more, equipment is microprocessor based and networked, requiring specialized skills traditionally not part of radio station engineering.
- As a result, in many cases, the bulk of repairs and upgrades can be carried out by personnel with IT skills.
- However, it's still high voltage RF going to the antenna and frequently high voltage AC/DC in the power supplies.



# **Nothing Ever Breaks**

- With higher levels of redundancy, equipment can frequently stay on air in spite of failures.
  - This frequently gets interpreted as "no failures", since there were no interruptions to the broadcast.
  - In spite of this, the need for ability to troubleshoot, work a soldering iron and perform complex repairs is still an important part of the job. Perhaps more important as these skills are typically only needed in urgent situations where a simple board swap won't solve the underlying problem.



# Why Nothing Ever Breaks

- As a rule, the sites with the fewest actual failures tend to be the ones where the work is put into protection and maintenance, rather than "putting out fires".
- More and more, in today's reality, less time is available for maintenance although there always seems to be time for the "fires"...



# "Other Duties, As Required"

- This frequently leads to a misconception that engineers can be less skilled, since they're frequently doing maintenance tasks cleaning filters, improving grounding, performing "check-ups" rather than actual repairs.
- In the ideal world, maintenance tasks should take up the vast majority of the engineer's time. If this were the case, the amount of repairs required would decrease dramatically.



# **Resulting Safety Concerns**

I have been getting calls from IT people who are struggling with transmitters that are beyond their level of education or understanding. Those people often do not have the Ohm's Law basic knowledge to help them think through component level troubleshooting problems. Any upcoming radio broadcast engineer needs to recognize this and train accordingly to be equipped mentally to deal with this when it occurs.

Mark Persons, "Where Have All the Engineers Gone?", Radio World, 16 May 2012

- More and more, the person tasked in maintaining the station may have a solid IT background, but have much less training and experience related to dealing with high voltage situations.
  - Power Supplies
  - Tube cavities
  - RF Filters, Phasors, Antenna Tuning Networks



# **Resulting Safety Concerns**

and the second	a second second		Construction of the	فيستعجز كفري
chie	r ena	ineer	found	dead
Cinc		- CCI	roana	

	sends thoughts and prayers to th	e family and friends of	, who was
chief engineer at	in	. The station plays "lite"	contemporary
Christian music a	nd has many translators including		

was found dead last Friday in the station's remote mountain transmitter shack.

Technical engineer for

Radio,

was found dead at the station's transmitter site

Title: Engineer Electrocuted Making Repairs At Post by: P

It is with sadness that I pass along a report seen on the evening news today out of **second bar**, Mississippi. Engineer **second bar died** died yesterday while working on the station's transmitter

# • More frequently, engineers are working alone, often after a full day at another job, bringing fatigue into the equation.





Photo of WISN phasor © www.oldradio.com



# 29CFR1910 says:

(3) Additional requirements for qualified persons. Qualified persons (i.e., those permitted to work on or near exposed energized parts) shall, at a minimum, be trained in and familiar with the following:

(i) The skills and techniques necessary to distinguish exposed live parts from other parts of electric equipment,

(ii) The skills and techniques necessary to determine the nominal voltage of exposed live parts, and

(iii) The clearance distances specified in §1910.333(c) and the corresponding voltages to which the qualified person will be exposed.



# **Costs of Fewer Engineers**

- Beyond the legal costs associated with a tragedy, the decline in available engineers comes with several other potential costs:
  - Cost of off-air time due to failures
    - Can tend to be higher as a result of lack of maintenance
  - Cost of repairs
    - Time and materials for in-house repair
    - Higher costs for factory repair/exchange... if available.
  - Increased time to repair failures by inexperienced personnel, with attendant risk of additional failures due to fatigue or misdiagnosis.



# **Proper Protection is Important**

• ESR (EH in the U.S.) rated footwear can keep you alive if you come in contact with a live circuit.



Electric Shock Resistant Boot / Electric Shock Resistant Footwear (ESR) Boots labeled "ESR" are manufactured to protect you from electric shock when working near electrical hazards. Testing concluded the leakage current did not exceed 1 mill ampere when applying an 18,000 volt / 60HZ electrical discharge to ground for one continuous minute.





# Ensure everything is discharged

• A ground stick can scare the pants off you if it hits a live circuit... but not nearly as badly as if YOU had hit that circuit.





### **Thermal Scans**







### **Safety is Key**

- Arc Flash
  - Can happen on any circuit handling over 125kVA
    - 50kW AM on 240VAC
    - Any AM transmitter 100kW or higher
    - 40kW FM on 240VAC





### Safety is Key



Lockout/tagout – it can save your life



### Safety Considerations

•Locking out a breaker while working on equipment ensures nobody else will be turning it on... while you're still in the rig.

•Transmitter interlocks are a safety feature, not an inconvenience to be bypassed and left bypassed.

•Measure before touching! Some systems have multiple AC mains connections (such as separate feeds for exciters).

•De-energize everything – breakers off, then ground stick.

•Airflow interlocks protect equipment



### Safety is Key

•Even after you've locked out the power source, a fast verification is a good idea (breakers can weld closed)





### Let's Be Careful Out There

• There is always the "potential" for danger.

• AC mains can be up to 600VAC... always measure any AC connection with a known working voltmeter before touching – use an appropriate meter.

• RF connections, especially in AM plants, can carry thousands of volts... use a grounding stick, or fashion one out of a set of jumper cables and a wooden broomstick... NEVER ASSUME THAT IT ISN'T HOT!!!

-A 300 foot insulated tower can pick up hundreds of volts of static on a windy day, even when disconnected from the transmitter.

-It can also pick up hundreds of volts of RF from another station.

-Messenger cables on long horizontal coax runs can be great antennas – and carry enough voltage to cause a very painful burn.

-Be careful of transmitters which may have bypassed interlocks or "modified" protection circuitry.

•Electrical circuits, especially high current DC supplies, have a lot of storage capacity to counteract mains sags. These can be hot for a long while after mains power is removed.



### Safety is Key

- Ensure use of proper safety equipment is mandatory
  - Ladders rated for working with electricity (and make sure ladders are used, don't stand on chairs!)
  - Equipment should be secured when not in use.





### **Troubleshooting/Maintenance**

- All legacy equipment (anything over 15 yrs old):
  - Check power supply wiring for cracked insulation
  - Check circuit breakers for mechanical integrity and operating temperature.





### **Troubleshooting/Maintenance**

- If a transmitter has a cover panel, LEAVE IT IN PLACE!
  - Safety
  - Airflow
  - Circulating currents



#### Unless there is a note specifying it's to be removed!

NV20/NV15 Installation Manual

UNPACKING AND POSITIONING

 Remove the grey, plastic power supply shipping panel in the lower, front compartment of the transmitter cabinet (covers the module power supplies). The panel is secured using M4 hardware.



### Hardware

 Compression connections must be checked periodically









Floodlights are relatively cheap

A well lit site is less likely to be robbed or vandalized.





There are two ways to prevent copper theft...

Bury it.

Make it less valuable or make it appear so.





- A well secured entrance creates peace of mind.
- If vandals or thieves can't get to your front door, it makes their task harder.





Use good quality locks and entrance hardware

Keyed alike is helpful

Security locks for which keys are registered (and can't easily be copied).





- A high quality peephole lets you see who's at the door.
- It's also harder to shoot through!







Obviously, a well fenced area is harder to get into!



- Anti-climb fencing can also be useful
- It also takes a lot longer to cut through





Web accessible cameras are cheap.

They won't prevent break-ins or theft, but they can provide a record.

In connection with motion sensors tied into the remote control, they can provide a way to see what's going on and provide faster police response. This can help limit damage and loss.







Someone Keeps Hacking Radio Stations To Play Donald Trump ... https://www.buzzfeed.com/\_/someone-keeps-backing-radio-stations-to-play-fuck-do







Login		
Systems > ext	əst	
User:		
Password:		
Screen Name:		
Remember me:		
	Enter user	& password
	Submit Res	set

220-FileZilla Server 0.9.55 beta
220-Grass Valley Automation FTP Server
220 You have full permissions, so please be careful!
530 Login or password incorrect!
214-The following commands are recognized:
 ABOR ADAT ALLO APPE AUTH CDUP CLNT CWD
 DELE EPRT EPSV FEAT HASH ...

nautel



$\leftrightarrow$ $\Rightarrow$ C $\triangle$					☆ 💩 🖸
👖 Apps 🕭 sa	ilesforce.com - Cus 📙 Tech St	uff 🦲 Sales 📙 Impo	ted 🐹 Winter Time - Gover	📙 SNMP stuff 🕒 Financing Quoter - N	» 📙 Othe
HOME LOO	CATION CONFIGURATION DEF	AULTS UPDATE REBO	OT Exstreamer 1	1000 MAC: 00:08:E1:02:C3:C6 FW VB1.06	
Studio T	ransmitter Link				B A R 🚺 🗙
Transmitter Decoder	BASIC SETTINGS			Help Basic Settings This section helps to setup a	fact startup configuration
Basic Settings Network	INCOMING STREAM			It allows the configuration of destination and of the <i>Incom</i> <i>Streaming</i> section help for fu	the first Outgoing Stream ing Stream socket. See
Streaming	Stream Method	URL	Port		
Audio I/O and Control Serial Security	Push(RTP) v	72.8.233.239	3030		
Apply					

Cancel





X-332					
Nautel-TPO: 11.00 KW Nautel-Refl: 0.06 KW	Sensor 1: 89.7 F Sensor 2: 89.7 F				
Mid Beacon Nor: Normal Mid Beacon Sou: Normal Upper Sides: Normal TopBeacon: Normal	NV10-Start: PULSE NV10-Stop: PULSE PS-1: 11KW PS-2: 2KW PS-3: 1KW				
	Wed, 13 Jun 2018 06:10:05				



nautel	Device: DYRF AM Transmitter         Data retrieved 2017-03-07T19:47:43         Status/Control       Presets       Preset Schedule       Meters       Alarms	About this equipment Save Event Log	1	
New Site	RF Power	On	Off	On
Home	Forward Power	6.10 kW	Increase	Decrease
	Reflected Power	10 W		
	System Control	Remote		
Equipment	Automation Control			
DYRF AM Transmitter	Automatic Preset Scheduler	Disabled	Disabled	Enabled
	Automatic Exciter Changeovers	Enabled	Disabled	Enabled
	Automatic PM Changeovers	Disabled	Disabled	Enabled
Administration	Active Preset	Manual Adjustment	1 •	Submit
Site Configuration	Active Exciter	A		
User Administration	Active PM	A/B		
	VSWR	1.08		
You are logged in as	Active Faults		Reset	
root	1	-7%	d Teach	
Logout				



192.168.0.1/a	ecipes 🛅 Tech Stuff 🛅 :	Sales	🗀 Imported 📓	How to use BlackBer	🗋 Seven Essent	ial Tim 🚫	Family tree view	Outlook Web App
	DIR-810L		SETUP	ADVANCED	TOOLS	;	STATUS	SUPPORT
	VIRTUAL SERVER PORT FORWARDING	The		on allows you to define a				Helpful Hints Check the Application Name drop down meru
	APPLICATION RULES	onlin	e services such as	ddress and Private LAN po FTP or Web Servers. Save Settings	ort if required. T	This feature is u	seful for hosting	for a list of predefined server types. If you select one of the predefined server types
	ACCESS CONTROL WEBSITE FILTER	-	- VIRTUAL SEI					click the arrow button next to the drop down menu to fill out the corresponding field.
	INBOUND FILTER				Port	Traffic Type		You can select a compu
	FIREWALL SETTINGS	_	Name SSH Access	Application Name 💌	Public Port	Protocol TCP 💌	Schedule Never 💌	from the list of DHCP clients in the Compute Name drop down men or you can manually en
	ADVANCED WIRELESS		IP Address	NAUTEL-C77ZTM	Private Port	6	Inbound Filter Deny Al 💌	the IP address of the computer at which you would like to open the
	WI-FI PROTECTED SETUP ADVANCED NETWORK		Name	Application Name	Public Port	Protocol TCP -	Schedule Always	specified port. Select a schedule for when the virtual server
	GUEST ZONE IPV6 FIREWALL		IP Address 192, 168.0, 100	NAUTEL-C77ZTM	Private Port	6	Inbound Filter	will be enabled. If you not see the schedule y need in the list of schedules, go to the
	IPV6 ROUTING		Name	Application Name	Public Port	Protocol TCP -	Schedule Always 💌	Tools
			IP Address 192, 168.0, 100	NAUTEL-C772TM	Private Port	6	Inbound Filter	Select a filter that restricts the Internet hosts that can access virtual server to hosts
			Name	Application Name	Public Port	Protocol	Schedule Always 💌	that you trust. If you on not see the filter you need in the list of filter go to the Advanced
			IP Address 192, 168-0, 100	NAUTEL-C77ZTM	Private Port	6	Inbound Filter	Inbound Filter scree and create a new filter More
			192.100.0.100	NAUTEL-C772TM.	3501	Protocol	Schadula	



#### In Summary:

- Use a firewall, block any ports that aren't essential to operation.
- CHANGE DEFAULT USERNAME / PASSWORD!!!
- For critical devices (most of them) consider a VPN or put them all on a non-internet connected local network, then use a VPN to access it.
- Alternately, use a product such as TeamViewer to access.



### To review:

- We are all doing more with less
  - Fewer resources
  - Lower budgets
  - Shrinking talent pool
- We need to carefully manage to ensure we're not overlooking critical points
  - Safety
  - Maintenance vs. "firefighting"
  - Potential legal implications
    - Protection of license
    - Avoiding liability



## Learn More / Stay in touch

- Nautel Waves Newsletter
   <u>https://www.nautel.com/newsletters/</u>
- Webinars <u>https://www.nautel.com/resources/webinars/</u>
- YouTube

https://www.youtube.com/user/NautelLtd











# **Nautel Major Product Families**





# Thank You

